



Nuevo Leben CS600X

Leben HI-FI STEREO

TARIFA 2019

CS-300F

3.290 € (IVA inc.)

STEREO POWER AMPLIFIER

Tubes employed	4 x JAN 6197, 2 x 17EW8(Hi-Fi)
Output Power	15W x 2
Frequency Response	15Hz - 100KHz (-2dB)
T.H.D.	0.7% (10W)
Input Sensitivity	600mV
Output Impedance	4/6/8 Ω (Selectable)
	300 Ω (Headphone)
Headphone Output	1000mW
Power Consumption	82W
Dimensions	(W) 360 □ (D) 270 □ (H) 140mm
Weight	11.0 Kg



CS-300X (S)

3.490 € (IVA inc.)

STEREO POWER AMPLIFIER

Tubes employed	4 x EL84(Sovtek), 2 x 12AX7WA
Output Power	15W x 2
Frequency Response	15Hz - 100KHz (-2dB)
T.H.D.	0.7% (10W)
Input Sensitivity	600mV
Output Impedance	4/6/8 Ω (Selectable)
	300 Ω (Headphone)
Headphone Output	1000mW
Power Consumption	82W
Dimensions	(W) 360 □ (D) 270 □ (H) 140mm
Weight	11.0 Kg



CS-600X

6.900 € (IVA inc.)

STEREO POWER AMPLIFIER

Used tubes	4 x 6CA7/EL34 (6L6WGC/5881 Option)
	2 x 12AU7A, 2 x 12BH7A
	1 x 6CM3/6DN3
Output Power	6CA7/EL34 : 28W x 2(MAX) at 1KHz.
	6L6WGC/5881 : 32W x 2(MAX) at 1KHz.
Input Sensitivity	900mV (at 20W)
Frequency Response	10Hz ~ 100KHz (-0.1.dB)
Power Consumption	195W Max
Dimensions	450(W) x 360(D) x 142(H)mm (Including knobs and other appendixes.)
Weight	23kg
Attachment	Detachable AC power cord



Novedad 2018

CS-1000P

10.490 €

STEREO POWER AMPLIFIER

Tubes employed	4 x KT120, 2 x 6922, 2 x 6CG7
Output Power	100W x 2 (Pentode) 70W x 2 (Triode)
F. Response	10Hz - 150KHz (-3dB) - Pentode
T.H.D. (Pentode)	0.4% (10W)
Input Impedance	100KΩ
Input Sensitivity	400mV(at 50W) - Pentode
Output Impedance	4/6/8/16 Ω (Selectable)
Power Consumption	270W(Max.)
Dimensions	455(W) X 200(H) X 335(D) mm
Weight	23.5Kg.



RS-28CX

6.990 €

PREAMPLIFIER

Tubes employed	2 x 6CG7, 2 x 12AT7, 1 x 5Y3WGT
Phono Stage	CR-Type, NON-NFB Gain : 20.2dB RIAA Curve : Less than ± 0.3dB Max. Input : 400mV (2KHz.)
Line Amplifier	Gain : 25.2dB Max. Output : 80V(Var & Fix) Output Impedance : 580Ω Remaining Noise : 0.03mV
Power Consumption	43W
Dimensions	352(W) X 175(H) X 240(D) (Main) 233(W) X 174(H) X 240(D) (PSU)
Weight	13.5Kg. (Total)



RS-30EQ

2.190 €

PREAMPLIFIER

Method	CR-type, NON-NFB Phono Stage
Tubes employed	2 x JAN 12AT7A, 1 x 6X5GT
Gain	23.5dB
RIAA Curve	Less than ± 0.2dB.
Input Impedance	47KΩ(Normal)
Max. Input	400mV (2KHz.)
Output Voltage	175mV
Power Consumption	17W
Dimensions	340(W) X 175(H) X 240(D) mm
Weight	6.0Kg.

